

DataSheet

The trusted go-to brand for fire extinguishers in the UK, Commander offers a comprehensive range of fire extinguishers. Now PFAS free across the entire range, time has proven the Commander range of fire extinguishers as a dependable choice for almost any situation – with reliable performance guaranteed.



PRODUCT CODE

FX-WWA-003-DCF | FX-PWA-006-FCF |
FX-PWA-009-FCF

PRODUCT GROUP

Commander® Extinguishers

DIMENSIONS (mm) (height x width x diameter)

FX-WWA-003-DCF: 435 x 240 x 140
FX-PWA-006-FCF: 475 x 275 x 180
FX-PWA-009-FCF: 550 x 300 x 210

WEIGHT

FX-WWA-003-DCF: 5.44kg
FX-PWA-006-FCF: 9.3kg
FX-PWA-009-FCF: 13.5kg

- Kitemarked to BS EN3
- MER/MED approved*
- UKCA and CE approved
- 35kVa Dielectric test certified
- Plastic base skirt for protection
- Polyethylene internal lining
- Full range of spare parts available
- 5-year warranty




*MED and MER applies to 6ltr and 9ltr only


WATER FIRE EXTINGUISHERS

A popular choice for Class A fires (combustible materials), Commander Water Fire Extinguishers work by cooling the fuel and ensuring it burns at a much slower pace until the fire is extinguished. With a low-cost price, ease of maintenance, and PFAS free contents, it's easy to see why water fire extinguishers are a preferred choice for many businesses.

The 3ltr Commander Water features a PFAS free additive, boasting a 13A fire rating, while the 6ltr and 9ltr Commander Water Fire Extinguishers are entirely plain water, featuring high-performance 21A and 27A fire ratings, respectively.

Technical Specification	FX-WWA-003-DCF	FX-PWA-006-FCF	FX-PWA-009-FCF
Capacity	3 litre	6 litre	9 litre
Fire Rating	13A	21A	27A
Extinguishing Medium	Water + additive	Water	Water
Working Pressure	12 bar @ 20°C	15 bar @ 20°C	15 bar @ 20°C
Temperature Range	+5°C to +60°C	+5°C to +60°C	+5°C to +60°C
Cylinder Material	Steel	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen	Nitrogen

 029 2086 8333

 029 2085 0627

 sales@checkfire.co.uk

 www.CheckFire.co.uk