

DataSheet

Wheeled extinguishers are designed for tackling large fires. Their huge capacity ensures a longer discharge time and higher rate of discharge than standard portable fire extinguishers, whilst the high quality trolley frames make the units easy to handle and enable fast deployment.

WHEELED EXTINGUISHERS

CO₂ Trolley Units

Available in both 10kg and 20kg, this unit combines high performance with compact dimensions. Ideal for significant flammable liquid fire risks and live electrical equipment risks, the extinguisher is easy to handle and operate.

Foam Trolley Units

AFF Foam trolley units are designed to cope with large Class A and Class B fires - for example fuel stations, large warehouses and manufacturing plants. Despite their size they are designed to be quickly moved and easily operated with one person.

Powder Trolley Units

Powder trolley units are tremendously effective, and their unsurpassed knock-down ability combined with the large capacity makes them suited for multi-class fire risks, for example large fuel stations, large manufacturing plants and heavy industry. They are robust and designed for a long service life.

Technical Specification	FX-CO2-010-DCF	FX-CO2-020-DCF	WFF50	WFP50	WFF100
Capacity	10kg	20kg	50ltr	50kg	100ltr
Extinguishing Medium	Carbon Dioxide	Carbon Dioxide	AFF Foam	ABC Powder	AFF Foam
Discharge Time	45s	75s	60s	41s	≥40s

029 2086 8333

029 2085 0627

sales@checkfire.co.uk

www.CheckFire.co.uk



COMMANDER®

PRODUCT CODE

FX-CO2-010-DCF | FX-CO2-020-DCF |
WFF50 | WFP50 | WFF100

PRODUCT GROUP

Wheeled Extinguishers

DIMENSIONS (mm) (height x diameter)

FX-CO2-010-DCF: 1180 x 340
FX-CO2-020-DCF: 1380 x 750
WFF50: 1120 x 600
WFP50: 1120 x 610
WFF100: 1065 x 400

WEIGHT

FX-CO2-010-DCF: 33kg
FX-CO2-020-DCF: 85kg
WFF50: 80kg
WFP50: 80kg
WFF100: 150kg

- Extremely portable and easy to handle
- High quality construction ensures a long service life
- Corrosion-resistant finish 5-year warranty