CheckFire GROUP

DataSheet

The home of innovation and elite performing PFAS-free fire extinguishers in the UK, CommanderEDGE boasts a number of reliable and extensively tested fire extinguishers.

SPECIALIST WATER FIRE EXTINGUISHERS

COMMANDER EDGE

As the cold weather sets in, water fire extinguishers in outdoor settings are at risk of their contents freezing – rendering them useless in the event of a fire. An anti-freeze extinguisher has an additive that means it can withstand low temperatures. To help support you and your customers through the winter months, we can supply our CommanderEDGE Water fire extinguishers pre-filled with anti-freeze ready for you.

The CommanderEDGE Water Mist consists of demineralised water, which works by producing a mist curtain, providing intense cooling to the fire, cutting off the oxygen supply and suffocating the flames.

Technical Specification	FX-WMS-006-CCF	FX-WLF-006-DCF	FX-WLF-009-DCF
Capacity	6 litre	6 litre	9 litre
Fire Rating	13A 40F	13A	21A
Extinguishing Medium	Water + Additive	Water + Anti-Freeze Additive	Water + Anti-Freeze Additive
Working Pressure	15 bar @ 20°C	12 bar @ 20°C	12 bar @ 20°C
Temperature Range	+5°C to +60°C	-10°C to +60°C	-10°C to +60°C
Cylinder Material	Steel	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen	Nitrogen

029 2086 8333
029 2085 0627
sales@checkfire.co.uk
www.CheckFire.co.uk

PRODUCT CODE
FX-WMS-006-CCF | FX-WLF-006-DCF | FX-WLF-009-DCF

PRODUCT GROUP
CommanderEDGE Extinguishers

DIMENSIONS (mm) (height x width x diameter)
FX-WMS-006-CCF: 435 x 240 x 140
FX-WLF-006-DCF: 531 x 245 x 162
FX-WLF-009-DCF: 610 x 320 x 180

WEIGHT
FX-WMS-006-CCF: 9.3kg
FX-WLF-006-DCF: 10.3kg
FX-WLF-009-DCF: 13.9kg

- Kitemarked to BS EN3*
- MER approved*
- UKCA and CE approved
- 35kVa Dielectric test certified
- Plastic base skirt for protection
- Polyethylene internal lining
- Full range of spare parts available
- 5-year warranty

**FX-WMS-006-CCF only*